

RA6

BI-DIRECTIONAL PAPER SPECIALTY FILAMENT TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

An industrial, fiberglass reinforced, smooth crepe paper backing with pressure-sensitive natural rubber adhesive. Medium strength and high adhesion. Manufactured to perform under a wide range of humidity and temperature conditions. Good adhesion and shear resistance offers a positive splice under constant web tension.

PRODUCT APPLICATIONS

A high-temperature splicing tape, used primarily in the floor covering and abrasive manufacturing industries. Can withstand temperature up to 400°F (204°C). Suitable for high temperature splicing of a variety of materials such as vinyl floor coverings and heavy kraft surfaces.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Smooth Crepe Paper
Adhesive	Natural Rubber / Resin
Reinforcement	Fiberglass
90° Adhesion to Steel (oz/in of width) (at 180° peel angle) ASTM D3330	54 (14.8 N/25mm)
Tensile Strength (lbs/in of width) Machine Direction Cross Direction	107 (468 N/25mm) 94 (411 N/25mm)
Elongation (% at break) ASTM D3759	3.4
Quick Stick (oz/in of width) To Kraft To Steel	6 (1.6 N/25mm) 24 (6.6 N/25mm)
Total Thickness (mils) ASTM D3652	12.4 (0.314mm)
Color	Natural



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 11/13